

LED RHYTHM

LED
PRECISE, HIGH-OUTPUT LIGHTING

Sky

LED FLOOD LIGHTING

- Clear vision: The stadium is as pure and clear as the starry sky, sublimating the visual experience and lighting up the luxury and elegance
- Unbounded light domain: Provides uniform lighting in a super wide range like the sky, leaving no dark areas.

100W, 120W, 150W, 180W, 200W

- **90° precise light control**

90° luminous angle control, precise lighting, reducing invalid diffusion, and more focused light.

- **Power at will**

80W-240W multiple power options, flexible adaptation to a variety of venues, and optimized power usage.

- **No-glare ingenuity**

Prism plate filters light, reducing up to 30% glare, comfortable lighting experience, and more enjoyable viewing.

- **Soft and frequency-free**

High-quality LED, stable and flicker-free, improves viewing comfort, and no burden on the eyes.

- **Perfect material**

Aviation-grade aluminum, pressure-resistant and wear-resistant, extremely durable, carrying the quality of high-end venues.

- **Reflective intelligent manufacturing**

High-reflective coating design improves light efficiency, uniform brightness, and reduces operating costs.



90° precise light control

90° luminous angle control, precise lighting, reducing invalid diffusion, and more focused light.

No-glare ingenuity

Prism plate filters light, reducing up to 30% glare, comfortable lighting experience, and more enjoyable viewing.

Soft and frequency-free



High-quality LED, stable and flicker-free, improves viewing comfort, and no burden on the eyes

ORDERING INFORMATION

SERIES	WATTS	CCT	OPTICS	INPUT PWR	Protection	Housing Material	DIMMING	FIELDS APPLICATION
Sky	100W	3000K	90°	120-277V	IP66	Die Cast Aluminum	0-10V Dimmable	Sports Lighting
	120W	4000K	120°	277-480 VAC				
	150W	5000K						
	180W	6500K						
	200W							

- 80 CRI CRI Standard
- Custom RAL Colors Require Additional Costs & Lead Times
- CM Mounting Standard

Distribution Types



LUMEN CHART

	3000K	4000K	5000K	6500K
100W	10000lm	10000lm	10000lm	10000lm
120W	12000lm	12000lm	12000lm	12000lm
150W	15000lm	15000lm	15000lm	15000lm
180W	18000lm	18000lm	18000lm	18000lm
200W	20000lm	20000lm	20000lm	20000lm

Due to continuous improvement and innovation, product appearance and specifications may change without notice. Actual performance may differ as a result of end-user environment and application.

EMAIL: SERVICE2-MARKET@LED RHYTHM.COM | WEBSITE: WWW.LEDRHYTHM.COM

SPECIFICATIONS

Life Time | Over 50,000 hrs.

Color Rendering Index (CRI) | >80

Operating Temp | -30°C – +45°C

Relative Humidity | 0-90% RH

Power Factor | ≥95%

Input Line Voltage | 120-277/277-480 VAC

Input Line Frequency | 50/60 Hz

LED Chips | OSRAM, PHILIPS

DIMMING | 0-10V Optional

LED Efficiency | 100 lm/w

WARRANTIES

SEE WEBSITE FOR DETAILS

5-Year

MATERIALS

Housing | Aluminum extrusion


Gasketing | Neoprene Rubber

Finish | Protective UV Stabilized Powdercoat

4000 Hour Salt Spray Tested to ASTM B117

Lens | PC

PRODUCT SIZE



100W-200W